



Logo Placements

1132 HV Jacket Class 3

Recommended logo placements

Heat seal

- 1 Left breast, 1 cm above pocket, maximum size 60x60 mm or 100x20 mm
- 2 Left sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
- 3 Right breast, maximum size 60x60 mm or 100x20 mm
- 4 Right sleeve, 5 cm below shoulder seam, maximum size 120x120 mm
- 6 Back, 2 cm below yoke seam, maximum size 180x280 mm,
logo might not be visible when the hood is down
- 23 Right breast, top of logo lining with placement, maximum size 120x120 mm
- 24 Left breast, top of logo in line with top of zipper, maximum size 60x80 mm
- 62 Back, 13 cm below yoke seam maximum size 250x280 mm



Maximum size of logo cm² to keep classification EN 20471

Size	cm ²	cm
XS	484	22x22
S	1290	35x35
M-4XL	2130	46x46



How to keep classification ISO EN 11612

Labels, badges, retro-reflective materials, transfers, etc., which are applied to the outermost surface of the garment, with an area > 10 cm² shall be tested in ISO 15025, Procedure A.



Add

B after the placement and it will be below the (1B)

Y and it will be turned from bottom to top

Z after the placement and it will be turned from top to bottom

